

NOISE ABATEMENT PROCEDURES

HAMILTON
HAMILTON ON

NOISE ABATEMENT PROCEDURES

GENERAL

Pursuant to CAR 602.105, the following procedures apply at Hamilton Airport.

DEPARTURE

RWY	VNAP
ALL RWYS	A or B

Departures not permitted on Rwy 06, between 2300 hours and 0700 hours local time unless authorized by Airport General Manager.

Runway 12:

Climb on track of 117° till "ZHM" NDB and 3000' ASL.

Runway 30:

Climb on rwy hdg to 1300' ASL. Turn left hdg 260° till abeam "ZHA" NDB. No right turn below 4000' ASL.

Rwys 06, 24:

Climb on runway heading to 3000' ASL before proceeding on course.

ARRIVAL

Arrivals not permitted on, and approaches not permitted to, Rwy 24 between 2300 hours and 0700 hours local time unless authorized by the Airport General Manager.

VISUAL ARRIVALS:

1. Aircraft 26,000 kg and over (max cert gross take-off weight) maintain 3000' ASL or above north of Rwy 12-30 except on final.
2. Remain on or above ILS glide slope or assumed 3° glide path.

PREFERENTIAL RUNWAYS

Between 2300 hours and 0700 hours local time, consistent with safety of operations, ATC will assign runways in the following order of priority.

ARRIVALS AND DEPARTURES

1. 12
2. 30
3. 24
4. 06

REVERSE THRUST

Consistent with safety of operations, pilots should minimize reverse thrust when using Rwys 12 and 30

TRAINING FLIGHTS

Training flights not permitted between 2300 hours and 0700 hours local time unless authorized by the Airport General Manager.

INQUIRIES

Contact the Airport General Manager at (905) 679-4151 between 0900 hours and 1700 hours local time.

NOISE ABATEMENT PROCEDURES

HAMILTON ON
HAMILTON

EFF 16 FEB 06

CHANGE: Rwy 12 track